



AR16JE-2

ARTICULATING BOOM LIFT



- Machines feature a large platform, a dual capacity design, large chassis tilt angle, and better adaptability to various working conditions.
- Proportional control achieves excellent synchronization of composite actions and realizes precise micro-motion control for comfortable operations.
- Remote software upgrades, parameter adjustments, and remote online diagnosis through telematics.
- Equipped with the intelligent self-diagnosis function, which facilitates convenient fault detection when the equipment arrives at or departs from the site.



ARTICULATION BOOM LIFT

SPECIFICATIONS

MODELS	AR16JE-2 (AR52JE-2)	
Measurements	Metric	Imperial
Work Height Max.	17.9m	58'9"
Platform Height Max.	15.9m	52'2"
Horizontal Outreach	9.4m	30'10"
Up and Over Height	7.4m	24'3"
Platform Length	1.83m	6'
Platform Width	0.76m	2'6"
A Stowed Length	7.56m	24'10"
Transport Length (jib tucked)	5.95m	19'6"
B Overall Width	2.3m	7'7"
C Stowed Height	2.26m	7'5"
Transport Height	2.68m	8'10"
D Wheelbase	2.25m	7'5"
E Ground Clearance	0.35m	1'2"

PRODUCTIVITY		
Platform Capacity (unrestricted)	250kg	551 lbs
Platform Capacity (restricted)	350kg	772 lbs
Max. Platform Occupancy	2(unrestricted)/3(restricted)	
Turntable Rotation	355°	355°
Drive Speed-Stowed	5km/h	3.1mph
Drive Speed-Raised	0.8km/h	0.5mph
Gradeability	45%	45%
Max. Wind Speed	12.5m/s	28mph
Turning Radius-Inside	2.9m	9'6"
Turning Radius-Outside	5.7m	18'8"
Max. Slope	5°/5°	5°/5°
Tire Type	Foam-filled	
Tire Models	315/55D20	
Ground Pressure, Tyres	415.3 kPa	60.2 psi

POWER		
Power Source	80V 173Ah	
HYDRAULIC SYSTEM		
Hydraulic Oil Volume	60L	15.9gal
WEIGHT		
Machine Weight	7,200kg	15,873 lbs


STANDARD FEATURES

Auto-leveling platform
Hydraulic rotating platform 180°
Full proportional joystick control
Descent alarm
Flashing beacons
Horn/Hour meter
Over-tilt protection system
Emergency stop button
Intelligent self-diagnosis function
Cylinder bellows
OTA remote upgrade
Dustproof components
Over-head anti-collision protection
Platform tool box

OPTIONAL

AC power to platform
Platform work light
Half-height mesh platform
Platform auxiliary guardrail
Platform pipe rack

MACHINE SIZE



Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.